




# Linear Drainage

***P6-GRATES*** Z886 & Z883  
Drainage System

---


*Perma-Trench*



## P6-DGE

### DUCTILE IRON SLOTTED GRATE

Dimensional Data (mm) are Subject to Manufacturing Tolerances and Change Without Notice



#### ENGINEERING SPECIFICATION - P6-DGE

- Slotted, Ductile Iron Grate
- 137mm wide by 506mm long
- Weighing 9.52kg per lineal metre
- Grate has an open area of 58843.33mm<sup>2</sup> per linear metre



#### DGE - Slotted Grate

Material:	Ductile Iron
Weight:	* 9.52kg
Open Area:	* 58843.33mm <sup>2</sup>
Slot Width/Hole Size:	12.7mm
Optional Frame:	HDF / HDG

\* = per lineal metre

#### LOAD CLASS RATING:

- Rated C - when used without frame assembly
- Rated F - when used with frame assembly



#### CERTIFICATIONS


- Independently certified to AS3996-2006
- AS1428.2 (A&M) Compliant



## P6-DOG

### DUCTILE IRON ORNAMENTAL GRATE

Dimensional Data (mm) are Subject to Manufacturing Tolerances and Change Without Notice



#### ENGINEERING SPECIFICATION - P6-DOG

- Ornamental, Ductile Iron Grate
- 137mm wide by 506mm long
- Weighing 7.29kg per lineal metre
- Grate has an open area of 35771.67mm<sup>2</sup> per lineal metre


#### DOG - Ornamental

Material:	Ductile Iron
Weight:	* 7.29kg
Open Area:	* 35771.67mm <sup>2</sup>
Slot Width/Hole Size:	6.35mm

\* = per lineal metre

#### LOAD CLASS RATING:

- Rated B - frame assembly not required



#### CERTIFICATIONS

- Independently certified to AS3996-2006
- AS1428.2 (A&M) Compliant



AS 1428.2  
Accessibility &  
Mobility Compliant



Bike Safe




Heel Proof

## P6-GDE

### GALVANISED DUCTILE IRON SLOTTED GRATE

Dimensional Data (mm) are Subject to Manufacturing Tolerances and Change Without Notice



#### ENGINEERING SPECIFICATION - P6-GDE

- Slotted, Galvanised, Ductile Iron Grate
- 136mm wide by 506mm long
- Weighing 9.25kg per lineal metre
- Grate has an open area of 58843.33mm<sup>2</sup> per lineal metre


#### GDE- Galvanised Slotted

Material:	Ductile Iron
Weight:	* 9.25kg
Open Area:	* 58843.33mm <sup>2</sup>
Slot Width/Hole Size:	12.7mm
Optional Frame:	HDF / HDG

\* = per lineal metre

#### LOAD CLASS RATING:

- Rated C - when used without frame assembly
- Rated F - when used with frame assembly



#### CERTIFICATIONS

- Independently certified to AS3996-2006
- AS1428.2 (A&M) Compliant






## P6-GHPDE

### GALVANISED DUCTILE IRON HEELPROOF LONGITUDINAL GRATE

Dimensional Data (mm) are Subject to Manufacturing Tolerances and Change Without Notice



#### ENGINEERING SPECIFICATION - P6-GHPDE

- HeelProof, Longitudinal, Galvanised, Ductile Iron Grate
- 137mm wide by 506mm long
- Weighing 14.14kg per lineal metre
- Grate has an open area of 46990.00mm<sup>2</sup> per lineal metre


#### GHPDE- HeelProof Galvanised Slotted

Material:	Ductile Iron
Weight:	* 14.14kg
Open Area:	* 46990.00mm <sup>2</sup>
Slot Width/Hole Size:	7.93mm
Optional Frame:	HDF / HDG

\* = per lineal metre

#### LOAD CLASS RATING:

- Rated C when used without frame assembly
- Rated F when used with frame assembly



#### CERTIFICATIONS


- Independently certified to AS3996-2006
- Independently certified to AS4586 (Slip)
- AS1428.2 (A&M) Compliant



## P6-HPDE

### DUCTILE IRON HEEL PROOF LONGITUDINAL GRATE

Dimensional Data (mm) are Subject to Manufacturing Tolerances and Change Without Notice



#### ENGINEERING SPECIFICATION - P6-HPDE

- Heel-Proof, Longitudinal, Ductile Iron Grate
- 137mm wide by 506mm long
- Weighing 14.4kg per lineal metre
- Grate has an open area of 46990mm<sup>2</sup> per lineal metre


#### HPDE - Heel-Proof Slotted

Material:	Ductile Iron
Weight:	* 14.14kg
Open Area:	* 46990mm <sup>2</sup>
Slot Width/Hole Size:	7.9375mm
Optional Frame:	HDF / HDG

\* = per lineal metre

#### LOAD CLASS RATING:

- Rated C when used without frame assembly
- Rated F when used with frame assembly



#### CERTIFICATIONS


- Independently certified to AS3996-2006
- Independently certified to AS4586 (Slip)
- AS1428.2 (A&M) Compliant



## P6-HPP

### HDPE HEELPROOF GRATE

Dimensional Data (mm) are Subject to Manufacturing Tolerances and Change Without Notice



#### CODES/COLOURS:

- P6-HPP-BLACK
- P6-HPP-DARK-GREY


**Note:** Additional Codes/Colours available by special order  
Additional lead times apply on Non-Stock Colours  
Non-Stock Colours: Blue, Green, Cream, White, Light Grey, Red, Yellow

#### ENGINEERING SPECIFICATION - P6-HPP

- HeelProof, HDPE (High Density Polyethylene) Grate
- 137mm wide by 506mm long
- Weighing 1.34kg per lineal metre <sup>2</sup>
- Grate has an open area of 30691.67mm<sup>2</sup> per lineal metre
- Frame optional (P886-SVF Stainless Steel Veneer Frame can be used as optional for aesthetics only)

#### LOAD CLASS RATING:

- Rated A - frame assembly not required



#### HPP - HeelProof Slotted HDPE

Material:	HDPE
Weight:	* 1.34kg
Open Area:	* 30691.67mm <sup>2</sup>
Slot Width/Hole Size:	6.35mm
Optional Frame:	SVF (aesthetics only) * = per lineal metre

#### CERTIFICATIONS

- Independently certified to AS3996-2006
- Independently certified to AS4586 (Slip)
- AS1428.2 (A&M) Compliant



AS 4586 Certified  
Non-Slip



AS 1428.2  
Accessibility &  
Mobility Compliant



Bike Safe




Heel Proof

## P6-RFGC

### REINFORCED SLOTTED GALVANISED STEEL GRATE

Dimensional Data (mm) are Subject to Manufacturing Tolerances and Change Without Notice



#### ENGINEERING SPECIFICATION - P6-RFGC

- Reinforced, Slotted, Galvanised steel grate
- 137mm wide by 1016mm long
- Weighing 7.14kg per lineal metre
- Grate has an open area of 25400.00mm<sup>2</sup> per lineal metre



#### RFGC - Reinforced Slotted Galvanised

Material:	Galvanised Mild Steel
Weight:	* 7.14kg
Open Area:	* 25400.00mm <sup>2</sup>
Slot Width/Hole Size:	9.525mm
Optional Frame:	HDF / HDG

\* = per lineal metre

#### LOAD CLASS RATING:

- Rated C - when used without frame assembly
- Rated D - when used without frame assembly



#### CERTIFICATIONS


- Independently certified to AS3996-2006
- AS1428.2 (A&M) Compliant



## P6-RFSC

### REINFORCED SLOTTED STAINLESS STEEL GRATE

Dimensional Data (mm) are Subject to Manufacturing Tolerances and Change Without Notice



#### ENGINEERING SPECIFICATION - P6-RFSC

- Reinforced slotted stainless steel grate
- 137mm wide by 1016mm long
- Weighing 7.74kg per lineal metre
- Grate has an open area of 25400.00mm<sup>2</sup> per lineal metre

#### RFSC - Reinforced Slotted Stainless

Material: 304 Stainless Steel

Weight: \* 7.74kg

Open Area: \* 25400.00mm<sup>2</sup>



Slot Width/Hole Size: 9.525mm

Optional Frame: HDS

\* = per lineal metre

#### LOAD CLASS RATING:

- Rated C - when used without frame assembly
- Rated D - when used without frame assembly



#### CERTIFICATIONS


- Independently certified to AS3996-2006
- AS1428.2 (A&M) Compliant



## P886-FGF

### DUCTILE IRON FRAME & GRATE

Dimensional Data (mm) are Subject to Manufacturing Tolerances and Change Without Notice



#### ENGINEERING SPECIFICATION - P886-FGF

- Ductile Iron Frame and grate
- 140mm wide by 508mm long
- Weighing 27.83kg per lineal metre
- Grate has an open area of 43391.67mm<sup>2</sup> per lineal metre


#### FGF - Ductile Iron

Material:	Ductile Iron
Weight:	* 27.83kg
Open Area:	* 43391.67mm <sup>2</sup>

\* = per lineal metre

#### LOAD CLASS RATING:

- Integral Frame



#### CERTIFICATIONS

- Independently certified to AS3996-2006
- AS1428.2 (A&M) Compliant



AS 1428.2  
Accessibility &  
Mobility Compliant



Bike Safe




Heel Proof

## P886-PVSG

### PAVER SLOT GALVANISED STEEL GRATE

Dimensional Data (mm) are Subject to Manufacturing Tolerances and Change Without Notice



#### ENGINEERING SPECIFICATION - P886-PVSG

- Galvanised Steel grate
- 137mm wide by 1016mm long
- Weighing 6.99kg per lineal metre
- Grate has an open area of 12700.00mm<sup>2</sup> per lineal metre


#### PVSG - Paver Slot

Material:	Galvanised Steel
Weight:	* 6.99kg
Open Area:	* 12700.00mm <sup>2</sup>

\* = per lineal metre

#### LOAD CLASS RATING:

- Rated C. - frame assembly not required



#### CERTIFICATIONS


- Independently certified to AS3996-2006
- AS1428.2 (A&M) Compliant



## P886-PVSS

### PAVER SLOT STAINLESS STEEL GRATE

Dimensional Data (mm) are Subject to Manufacturing Tolerances and Change Without Notice



#### ENGINEERING SPECIFICATION - P886-PVSS

- Stainless Steel grate
- 137mm wide by 1016mm long
- Weighing 6.85kg per lineal metre
- Grate has an open area of 12700.00mm<sup>2</sup> per lineal metre


#### PVSS- Paver Slot

Material:	Stainless Steel
Weight:	* 6.85kg
Open Area:	* 12700.00mm <sup>2</sup>

\* = per lineal metre

#### LOAD CLASS RATING:

- Rated C. - frame assembly not required



#### CERTIFICATIONS

- Independently certified to AS3996-2006
- AS1428.2 (A&M) Compliant







**ZURN AUSTRALIA**  
49 LAKESIDE DRIVE BROADMEADOWS VIC 3047  
PHONE: 1300 00 ZURN FAX: 03 9357 1455

---