





Flo-Thru Drainage Systems

Z887-6

100MM CLEAR OPENING INLINE DRAINAGE PIT

Dimensional Data (mm) are Subject to Manufacturing Tolerances and Change Without Notice SPECIFYING ENGINEER IS RESPONSIBLE FOR CONCRETE ENCASEMENT AND REINFORCING BASED UPON APPLICATION AND LOCAL CODES





+ Actual channel length is 527mm

ENGINEERING SPECIFICATION - Z887-6X20

- Drainage Pits are 527mm long, 159mm wide overall and 508mm deep
- Pits are made of 0% water absorbent High Density Polyethylene (HDPE)
- Pits mechanically lock into the concrete surround a minimum of every 254mm
- Pits weigh less than 7.70kg
- Drainage Pits come with rebar clips standard to secure pit in its final location

GRATES - Z886

See Grates Specification sheets for details		
GRATES	CLASS W/O FRAME	CLASS W/FRAME
P6-HPP	Α	Α
P6-DGC	С	-
P6-GDC	С	-
P6-DGE	-	F
P6-HDPE	С	F
P6-RFGC	С	D
P6-RFSC	С	D
P886-FGF	-	G
P886-PVSG	С	N/A
P886-PVSG	С	N/A

ACCESSORIES CODES - Z887

CODE	DESCRIPTION
P887-INLET-6-NS	Inlet Adaptor - Z886

SPEC2017 Z887-6 ZURN.COM.AU