
Z-882 Perma-Trench HDPE Systems

235mm Clear Opening




Channel Data

Trench	Trench Type	Shallow Invert	Deep Invert	Max. Flow Rate	Weight (Less Grate)	Length
Part#	P/N	mm	mm	LPS	Kg	mm
8201	Presloped	159	184	35	30.8	2500
8202	Presloped	184	210	49	30.8	2500
8203	Presloped	210	235	63	31.8	2500
8203N	Neutral	235	235	71	-	2500
8204	Presloped	235	260	78	32.7	2500
8205	Presloped	260	286	93	34	2500
8206	Presloped	286	311	108	34.9	2500
8206N	Neutral	311	311	78	-	2500
8207	Presloped	311	337	123	35.8	2500
8208	Presloped	337	362	139	36.3	2500
8209	Presloped	362	387	155	37.7	2500
8209N	Neutral	387	387	84	-	2500
8210	Presloped	387	413	170	38.6	2500
8211	Presloped	413	438	186	39.5	2500
8212	Neutral	438	464	202	40.4	2500


Disclaimer: Zurn Australia and our suppliers reserve the right to vary specifications or delete models from the range without prior notification. Dimensions listed are correct at time of publication however Zurn Australia takes no responsibility for printing errors.

Australian Standards - AS3996-2006



User & Legislative Requirements





ZURN.COM.AU