

FLUSHING SYSTEMS

Product Guide











CONTENTS CONVERSION VALVES MAINS PRESSURE VALVES LOW PRESSURE VALVES 13 SENSAFLUSH 17 ACCESS PANELS 18



49 LAKESIDE DRIVE BROADMEADOWS VIC 3047 1300 00 ZURN salesaus@zurn.com zurn.com.au PRODUCT CODE Z-6000 PRODUCT CODE Z-6154

CONVERSION EXPOSED FLUSH VALVE

CONVERSION CONCEALED FLUSH VALVE





The Zurn Z-6000 series are fitted with custom inlet adaptors to suit older flush valve models that are no longer operational.

SPECIFICATIONS:

- > Conversion flush valve for pans / urinals
- > Standard pan connection and urinal connection available
- > Min water supply pressure 40kPa
- > Max water supply pressure 300kPa
- > Flush volume adjustable
- > Flow rate required 1.5L per sec
- > WELS 1 Star 5.5L
- > Watermarked Approved WM-00307

PRODUCTS:

Z-6000G Zurn to Gloria pan conversion valveZ-6000H Zurn to Hush pan conversion valve

Z-6000U Zurn to Unibra pan conversion valve


Z-6000P Zurn to Pubco pan conversion valve

Z-6000S Zurn to Sloan pan conversion valve


OPTIONS:

- > FPCP-40 40x450x450mm chrome plated copper flush pipe
- > P6000-M-ADA-DF Exposed dual flush
- > Z-6000LU Low pressure 2.0L per sec
- > (Product Code)U Urinal connection













The Zurn Z-6154 series are fitted with custom inlet adaptors to suit older flush valve models that are no longer operational.

SPECIFICATIONS:

- > Conversion flush valve for pans / urinals
- > Standard pan connection and urinal connection available
- > Min water supply pressure 40kPa
- > Max water supply pressure 300kPa.
- > Flush volume adjustable
- > Flow rate required 1.5L per sec
- > WELS 1 Star 5.5L
- > Watermarked Approved WM-00307

PRODUCTS:

Z-6154G Zurn to Gloria pan conversion valveZ-6154H Zurn to Hush pan conversion valve

Z-6154U Zurn to Unibra pan conversion valve

Z-6154P Zurn to Pubco pan conversion valve

Z-6154S Zurn to Sloan pan conversion valve

- > FPCP-40 40x450x450mm chrome plated copper flush pipe
- > SS-300 300x300mm stainless steel panel
- > (product code)U Urinal connection

PRODUCT CODE ZDF-6154 PRODUCT CODE ZH-6154

CONVERSION CONCEALED DUAL FLUSH VALVE

CONVERSION CONCEALED HYDRAULIC FLUSH VALVE





The Zurn ZDF-6154 series are fitted with custom inlet adaptors to suit older flush valve models that are no longer operational.

SPECIFICATIONS:


- > Conversion flush valve for pans / urinals
- > Standard pan connection and urinal connection available
- > Min water supply pressure 40kPa
- > Max water supply pressure 300kPa.
- > Flush volume 6 / 3L adjustable
- > Flow rate required 1.5L per sec
- > WELS 3 Star 6 / 3L
- > Watermarked Approved WM-00307

PRODUCTS:


ZDF-6154G Zurn to Gloria pan conversion valve ZDF-6154H Zurn to Hush pan conversion valve ZDF-6154U Zurn to Unibra pan conversion valve ZDF-6154P Zurn to Pubco pan conversion valve ZDF-6154S Zurn to Sloan pan conversion valve

OPTIONS:

- > ZDF-6152BX12 300x300mm stainless steel panel and frame
- > ZDF-6152P 300x300mm s/s panel
- > FPCP-40 40x450x450mm s/s flush pipe
- > PH-6000-HYL-FF-SD Small diameter flush buttons
- > (product code)U Urinal connection











The Zurn ZH-6154 series are fitted with custom inlet adaptors to suit older flush valve models that are no longer operational.

SPECIFICATIONS:

- > Conversion flush valve for pans / urinals
- > Standard pan connection and urinal connection available
- > Min water supply pressure 40kPa
- > Max water supply pressure 300kPa.
- > Flush volume 5.5L
- > Flow rate required 1.5L per sec
- > WELS 1 Star 5.5L
- > Watermarked Approved WM-00307

PRODUCTS:

ZH-6154G Zurn to Gloria pan conversion valve ZH-6154H Zurn to Hush pan conversion valve ZH-6154U Zurn to Unibra pan conversion valve ZH-6154P Zurn to Pubco pan conversion valve ZH-6154S Zurn to Sloan pan conversion valve

OPTIONS:

> (product code)U - Urinal connection

PRODUCT CODE ZH-6140XL PRODUCT CODE ZH-6195XL

MAINS PRESSURE HYDRAULIC CONCEALED FLUSH VALVE

CONCEALED FLUSH VALV




Zurn ZH-6140XL mains pressure hydraulic concealed flush valve to suit back entry slab type urinals. One flush valve required for every 1.8 metres of urinal length to AS 3500.1.2.1995 Table 9.2

SPECIFICATIONS:

- > Min water supply pressure 175kPa
- > Max water supply pressure 500kPa.
- > Flush volume 2L
- > Flow rate required 1.5L per sec
- > Inlet connection 25mm BSP
- > Watermarked Approved WM-00307


OPTIONS:

- > ZDF-6152BX12 300x300mm stainless steel panel and frame
- > SS-300H18 300x300mm stainless steel panel w/ 18mm centre hole
- > SSP-300 300x300mm stainless steel panel and frame w/ concealed fixings



MAINS PRESSURE HYDRAULIC CONCEALED FLUSH VALVE







Zurn ZH-6195XL mains pressure hydraulic concealed flush valve to suit wall hung single urinals. Optimum pressure for certain brands of open rim urinals is 250kPa, achieved by Wilkins #600 or NR3 series.

SPECIFICATIONS:

- > Min water supply pressure 175kPa
- > Max water supply pressure 350kPa.
- > Flush volume 5.5L
- > Flow rate required 1.5L per sec
- > Inlet connection 20mm BSP
- > WELS 3 Star 2L
- > Watermarked Approved WM-00307

- > ZDF-6152BX12 300x300mm stainless steel panel and frame
- > SS-300H18 300x300mm stainless steel panel w/ 18mm centre hole
- > SSP-300 300x300mm stainless steel panel and frame w/ concealed fixings


PRODUCT CODE ZH-6152XL PRODUCT CODE Z-6010XL

MAINS PRESSURE HYDRAULIC CONCEALED FLUSH VALVE

MAINS PRESSURE EXPOSED FLUSH VALVE







FEATURES:

- > Chloramine resistant
- > Dual seal diaphragm
- > One-piece hex coupling nut and adjustable tailpiece


SPECIFICATIONS:

- > Min water supply pressure 175kPa
- > Max water supply pressure 500kPa.
- > Flush volume 5.5L
- > Flow rate required 1.5L per sec
- > Inlet connection 25mm BSP
- > WELS 1 Star 5.5L
- > Watermarked Approved WM-00307


OPTIONS:

- > ZDF-6152BX12 300x300mm stainless steel panel and frame
- > SS-300H18 300x300mm stainless steel panel w/ 18mm centre hole
- > SSP-300 300x300mm stainless steel panel and frame w/ concealed fixings











Zurn Z-6010XL mains pressure exposed flush valve to suit toilet pans. .

FEATURES:

- > Chloramine resistant
- > Dual seal diaphragm with clog-resistant bypass and quiet diaphragm-type
- > Chrome plated flushometer valve with polished exterior

SPECIFICATIONS:

- > Non-hold open and no-leak handle
- > High back pressure vacuum breaker
- > Control stop has internal siphon-guard protection
- > Chloramine resistant internal seals
- > Includes flush pipe
- > Flush volume 5.5L
- > Inlet connection 25mm BSP
- > Watermarked Approved WM-00307

PRODUCT CODE ZST-6195XL PRODUCT CODE ZDFST-6152XL

MAINS PRESSURE SINGLE URINAL FLUSH VALVE

MAINS PRESSURE DUAL **FLUSH VALVE**





The Zurn ZST-6195XL mains pressure solenoid type single flush valve suitable for connection to Warden water management system or similar.


SPECIFICATIONS:

- > Min water supply pressure 150kPa
- > Max water supply pressure 350kPa.
- > Flush volume 1.5L adjustable
- > Flow rate required 1.5L per sec
- > Inlet connection 20mm BSP
- > Watermarked Approved WM-00307

OPTIONS:

> ZST-300 - stainless steel panel to suit piezo button







25MM INLET

624mm

273mm MAX

WALL





operating system. Also suitable for connection to building management systems. OPTIONAL WALL PLATES? **SPECIFICATIONS:** 121mm */-13mm H $O \Phi$

VACUUM BREAKER


AND FLUSHPIPE

> Min water supply pressure - 150kPa

WaterMark

- > Max water supply pressure 500kPa.
- > Flush volume 6 / 3L adjustable
- > Flow rate required 1.5L per sec
- > Inlet connection 25mm BSP
- > WELS 3 Star 6 / 3L
- > Watermarked Approved WM-00307

- > Warden operating system
- > Piezo buttons
- > SSP-300 300x300mm stainless steel panel and frame w/ concealed fixings
- > ZDFP-300 stainless steel panel to suit piezo buttons



PRODUCT CODE ZDF-6152XL PRODUCT CODE Z-6000L

MAINS PRESSURE DUAL FLUSH VALVE

LOW PRESSURE EXPOSED FLUSH VALVE





Zurn ZDF-6152XL mains pressure dual flush valve to suit back entry toilet pans.

SPECIFICATIONS:


- > Min water supply pressure 150kPa
- > Max water supply pressure 500kPa.
- > Flush volume 6 / 3L adjustable
- > Flow rate required 1.5L per sec
- > Inlet connection 25mm BSP
- > WELS 3 Star 6 / 3L
- > Watermarked Approved WM-00307

OPTIONS:


- > ZDF-6152P 300x300mm stainless steel panel
- > ZDF-6152BX12 300x300mm stainless steel panel and frame
- > SSP-300 300x300mm stainless steel panel and frame w/ concealed fixings
- > ZDFPA-SS 330x330mm stainless steel satin panel and frame w/ concealed fixings
- > Additional button blocks available

Please note: button blocks not included













Zurn Z-6000L low pressure exposed flush valve to suit 5L back entry toilet pans.

SPECIFICATIONS:

- > Min water supply pressure 40kPa
- > Max water supply pressure 300kPa.
- > Flush volume adjustable
- > WELS 1 Star 5.5L
- > Watermarked Approved WM-00307

- > FPCP-40 40x450x450mm chrome plated copper flush pipe
- > P6000-M-ADA-DF Exposed dual flush

LOW PRESSURE CONCEALED FLUSH VALVE

LOW PRESSURE HYDRAULIC CONCEALED FLUSH VALVE







Z-6152L

Z-6195L

The Zurn low pressure concealed flush valves with isolation valve to suit.

SPECIFICATIONS:

- > Min water supply pressure 40kPa
- > Max water supply pressure 300kPa.
- > Flush volume 6L toilet pans / 2L urinals
- > Inlet connection 40mm BSP female
- > Flush valve outlet suits 40mm flush pipe
- > Z-6152L WELS 1 Star 5.5L
- > Z-6195L WELS 3 Star 1.5L
- > Watermarked Approved WM-00307


PRODUCTS:

Z-6152L back entry toilet pansZ-6195L wall hung urinals


OPTIONS:


- > SS-300H38 300x300mm stainless steel panel w/ 38mm centre hole
- > SSP-300 300x300mm stainless steel panel and frame w/ concealed fixings
- > FPCP-40 40x450x450mm chrome plated copper flush pipe

















ZH-6152L

ZH-6195L

The Zurn low pressure concealed flush valves with push button and isolation valve to suit back entry toilet pans.

SPECIFICATIONS:

- > Min water supply pressure 40kPa
- > Max water supply pressure 300kPa.
- > Flush volume 6L toilet pans / 2L urinals
- > Inlet connection 40mm BSP female
- > Flush valve outlet suits 40mm flush pipe > ZH-6152L - WELS - 1 Star - 5.5L
- > ZH-6195L WELS 3 Star 1.5L
- > Watermarked Approved WM-00307

PRODUCTS:

ZH-6152L back entry toilet pans ZH-6195L wall hung urinals

- > ZH-6152BX12 300x300mm stainless steel panel and frame
- > SS-300H18 300x300mm stainless steel panel w/ 18mm centre hole
- > SSP-300 300x300mm stainless steel panel and frame w/ concealed fixings
- > FPCP-40 40x450x450mm chrome plated copper flush pipe

PRODUCT CODE ZDF-6152L PRODUCT CODE SS100KIT

LOW PRESSURE DUAL FLUSH VALVE

SENSAFLUSH SENSOR KIT





The Zurn ZDF-6152L low pressure dual flush valve to suit back entry pans.


SPECIFICATIONS:

- > Min water supply pressure 50kPa
- > Max water supply pressure 300kPa.
- > Flush volume 6 / 3L adjustable
- > Flow rate required 1.5L per sec
- > WELS 3 Star 6 / 3L
- > Watermarked Approved WM-00307

OPTIONS:

- > ZDF-6152PS 200x100mm stainless steel panel
- > ZDF-6152P 300x300mm stainless steel panel
- > ZDF-6152BX12 300x300mm stainless steel panel and frame
- > FPCP-40 40x450x450mm chrome plated copper flush pipe














- > Adjustable cycle times, flush duration and after hours flushing
- > Microwave sensor detects movement before initiating flush cycle

PRODUCTS:


SS100 Sensor Unit SS100KIT Installation Kit



SINGLE ACCESS PANELS

DUAL ACCESS PANELS






PRODUCT CODE SSP-300

SPECIFICATIONS:

- > 300x300mm stainless steel
- > Access panel w/ concealed fixings
- > Suits Zurn single flush valves

OPTIONS:

- > Powder coated
- > No centre hole




PRODUCT CODE SSP-300DF

SPECIFICATIONS:

- > 300x300mm stainless steel
- > Access panel w/ concealed fixings
- > Suits Zurn dual flush valves

OPTIONS:

> Powder coated




PRODUCT CODE ZH-6152BX12

SPECIFICATIONS:

- > 300x300mm stainless steel
- > Access panel and mounting frame
- > Suits Zurn single flush valves

OPTIONS:

- > Powder coated
- > Vandal proof panel screws



PRODUCT CODE ZDF-6152BX12

SPECIFICATIONS:

- > 300x300mm stainless steel
- > Access panel and mounting frame
- > Suits Zurn dual flush valves

- > Powder coated
- > Vandal proof panel screws

SMALL DIAMETER DUAL FLUSH BUTTONS



PH-6000-HYL-HF-SD

PH-6000-HYL-FF-SD

The small diameter dual flush buttons have a brass body with a polished chrome plated finish. A modern design suitable for any bathroom layout. Custom made mounting plates are available.

Flush valves suitable for dual flush buttons:

- > ZDF-6152L-SD
- > ZDF-6152XL-SD
- > ZDF-6154G-SD
- > ZDF-6154H-SD
- > ZDF-6154P-SD > ZDF-6154S-SD
- > ZDF-6154U-SD

Flush valves suitable for single flush button:

> ZH-6152XLC-SD

OPTIONS:

- > PH-6000-HYL-HF-SD Half-flush button
- > PH-6000-HYL-FF-SD Full-flush button
- > ZDF-6152PSH38.5 200x100mm stainless steel slim panel
- > SSP-300-DFH38.5 300x300mm stainless steel panel



Exploded view (front)

DUAL FLUSH PANELS

The range of dual flush push panels use a rocker system of activation giving it a very low profile and modern look. Suitable for use with ZDF-6152XL or ZDF-6152L Zurn dual flush valves.

When specifying, ensure both the valve and push panel/button have been specified seperately.



ZDFPA-SS-COMP

SPECIFICATIONS:

- > Dual flush panel assembly
- > 330x330mm stainless steel panel & frame
- > Satin finish
- > Concealed fixing

PUSH PANEL OPTIONS:

- > ZDFPA-SW-COMP white push plate
- > ZDFPA-SWB-COMP braille push plate



ZDFPA-SW-COMP



ZDFPA-SWB-COMP

PLEASE NOTE: ADDITIONAL PANEL OPTIONS AVAILABLE ON SPECIAL ORDER ONLY. ADDITIONAL LEAD TIMES APPLY.



ZURN AUSTRALIA

ABN: 12 164 922 758



PHONE

1300 00 ZURN

EMAIL

salesaus@zurn.com

HEAD OFFICE

VICTORIA

49 Lakeside Drive Broadmeadows VIC 3047 Fax: +61 3 9357 1455

QUEENSLAND 3 / 11 Breene Place Morningside QLD 4170 Fax: +61 7 3396 7066 NEW SOUTH WALES Unit 6 / 3-11 Hallmark Street Pendle Hill NSW 2145 Fax: +61 2 9631 2065 WESTERN AUSTRALIA 398 Victoria Road Malaga WA 6090 Fax: +61 8 9249 8922 NORTHERN TERRITORY Unit 4 / 10 Witte Street Winnellie NT 0820 Fax: +61 8 8947 0036